



○ GENSET MODEL

	Prime	JGP1000P1	
	Standby	JGP1100E1	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime Power	KVA	1000	N/A
	KW	800	N/A
Standby Power	KVA	1100	N/A
	KW	880	N/A
Gross Engine Power	KW	969	N/A
	hp	1299	N/A

*Rating at 0.8 Power Factor

Fuel Consumption @ 50% load	L/hr	109.4	N/A
@ 75% load	L/hr	157	N/A
@ 100% load	L/hr	215.4	N/A

○ TECHNICAL DATA

Perkins Engine Model	4008TAG2A		
Leroy Somer / Stamford Alternator Model	LSA50.2S4		
Number of Cylinders	8 in line		
Cubic Capacity	Litres	30.6	
	cu.in	1864.9	
Bore	mm	160	
	in	6.3	
Stroke	mm	190	
	in	7.5	
Fuel Tank Capacity	Lit	N/A	

○ DIMENSIONS & WEIGHT

Length	cm	480
Width	cm	204
Height	cm	224
Weight	Kg	7550

Prime Rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power in the event of utility power failure. No overload is permitted on these ratings.



Rua Pedro de Castro vandunen (Loy) entre a retunda de entrada do Nova Vida e a entrada do Gamek, Kilamba Kiaxi

Fax: 222 383 187
Tel: 912 503 137
923 320 418
923 343 142

E-Mail: beledear@gmail.com
Web: www.beledear.com