



Perkins UK



○ GENSET MODEL

	Prime	JGP20	
	Standby	JGP22E	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime Power	KVA	20	22.5
	KW	16	18
Standby Power	KVA	22	25
	KW	17.6	20
Gross Engine Power	KW	20.6	24.3
	hp	28	33

\*Rating at 0.8 Power Factor

Fuel Consumption @	50% load	L/hr	2.9	3.4
	75% load	L/hr	3.9	4.6
	100% load	L/hr	5.4	6.1

○ TECHNICAL DATA

Perkins Engine Model	404D - 22G		
Leroy Somer / Stamford Alternator Model	LSA42.2S5 / BCI 184E		
Number of Cylinders	3 in line		
Cubic Capacity	Litres	2.2	
	cu.in	135.2	
Bore	mm	84	
	in	3.3	
Stroke	mm	100	
	in	3.9	
Fuel Tank Capacity	Lit	46	

○ DIMENSIONS & WEIGHT

Length	cm	140
Width	cm	52
Height	cm	128
Weight	Kg	475

Prime Rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power in the event of utility power failure. No overload is permitted on these ratings.



Rua Pedro de Castro vandunen (Loy) entre a retunda de entrada do Nova Vida e a entrada do Gamek, Kilamba Kiayi

Fax: 222 383 187  
Tel: 912 503 137  
923 320 418  
923 343 142

E-Mail: nabil06@hotmail.com  
www.beledear.com