



○ GENSET MODEL

	Prime	JGP200H2	
	Standby	JGP220HE2	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime Power	KVA	200	225
	KW	160	180
Standby Power	KVA	220	250
	KW	176	200
Gross Engine Power	KW	228.5	246.8
	hp	306	331

*Rating at 0.8 Power Factor

Fuel Consumption @ 50% load	L/hr	25.6	30.7
@ 75% load	L/hr	37.4	44.6
@ 100% load	L/hr	49.4	56.6

○ TECHNICAL DATA

Perkins Engine Model	1306C-E87TAG4		
Leroy Somer / Stamford Alternator Model	LSA46.2M5 / UCI274H		
Number of Cylinders	6 in line		
Cubic Capacity	Litres	8.7	
	cu.in	531	
Bore	mm	116.6	
	in	4.6	
Stroke	mm	136	
	in	5.4	
Fuel Tank Capacity	Lit	385	

○ DIMENSIONS & WEIGHT

Length	cm	290
Width	cm	99
Height	cm	170
Weight	Kg	2052

Prime Rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power in the event of utility power failure. No overload is permitted on these ratings.



Rua Pedro de Castro vandunen (Loy) entre a retunda de entrada do Nova Vida e a entrada do Gamek, Kilamba Kixi

Fax: 222 383 187
Tel: 912 503 137
923 320 418
923 343 142

E-Mail: nabil06@hotmail.com
www.beledear.com