



○ GENSET MODEL

	Prime	JGP80P1	
	Standby	JGP88E1	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime Power	KVA	80	90
	KW	64	72
Standby Power	KVA	88	100
	KW	70.4	80
Gross Engine Power	KW	80.7	92.6
	hp	108	124

*Rating at 0.8 Power Factor

Fuel Consumption @	50% load	L/hr	9.5	11.6
	75% load	L/hr	13.6	16.2
	100% load	L/hr	18	21.3

○ TECHNICAL DATA

Perkins Engine Model	1104A-44TG2		
Leroy Somer / Stamford Alternator Model	LSA43.2L8 / UC224G		
Number of Cylinders	4 in line		
Cubic Capacity	Litres	4.4	
	cu.in	268.5	
Bore	mm	105	
	in	4.1	
Stroke	mm	127	
	in	5	
Fuel Tank Capacity	Lit	128	

○ DIMENSIONS & WEIGHT

Length	cm	202
Width	cm	73
Height	cm	124
Weight	Kg	1010

Prime Rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power in the event of utility power failure. No overload is permitted on these ratings.



Rua Pedro de Castro vandunen (Loy) entre a retunda de entrada do Nova Vida e a entrada do Gamek, Kilamba Kixi

Fax: 222 383 187

Tel: 912 503 137

923 320 418

923 343 142

E-Mail: nabil06@hotmail.com

www.beledear.com